

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: T25 SERIE/SERIES
Print date 16.07.2020
Version 8.8 Revision date 23.05.2020 EN
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): T25
Trade name/designation SERIE/SERIES

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Printing ink/-lacquer

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

A. M. Ramp & Co. GmbH
RUCC Druckfarben Telephone: +49.61 98.30 40
Lorsbacher Str. 28 Telefax: +49.61 98.3 22 88
D-65817 Eppstein

Department responsible for information:

E-mail info@ruco-inks.com

1.4. Emergency telephone number

Emergency telephone number +49.61 98.30 40
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

| | | |
|--------------------------|--|--|
| Flam. Liq. 3 / H226 | Flammable liquids | Flammable liquid and vapour. |
| STOT SE 3 / H335 | Specific target organ toxicity (single exposure) | May cause respiratory irritation. |
| STOT SE 3 / H336 | Specific target organ toxicity (single exposure) | May cause drowsiness or dizziness. |
| Aquatic Chronic 3 / H412 | Hazardous to the aquatic environment | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226 Flammable liquid and vapour.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370 + P378 In case of fire, use sand, extinguishing powder or alcohol resistant foam.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazard components for labelling

hydrocarbons, C9, aromatics

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description Solvent containing pigment dispersion on resin basis

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

| EC No. CAS No. INDEX No. | REACH No. Designation classification: // Remark | weight-% |
|---|--|-----------|
| 918-668-5 64742-95-6 | 01-2119455851-35-XXXX hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336 | 20 - 25 |
| 215-535-7 1330-20-7 601-022-00-9 | 01-2119488216-32-XXXX Xylene Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / STOT RE 2 H373 / STOT SE 3 H335 | 5 - 10 |
| 259-370-9 54839-24-6 603-177-00-8 | 01-2119475116-39-XXXX 2-ethoxy-1-methylethyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336 | 5 - 10 |
| 202-849-4 100-41-4 601-023-00-4 | 01-2119489370-35-XXXX ethylbenzene Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 2 H225 | 1 - 2,5 |
| 200-663-8 67-66-3 602-006-00-4 | 01-2119486657-20-XXXX Trichloromethane Carc. 2 H351 / Repr. 2 H361 / Acute Tox. 3 H331 / Acute Tox. 4 H302 / STOT RE 1 H372 / Eye Irrit. 2 H319 / Skin Irrit. 2 H315 | 0,3 - 0,5 |

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Article No.: T25 SERIE/SERIES
Print date 16.07.2020
Version 8.8 Revision date 23.05.2020

EN
Page 3 / 10

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: T25 SERIE/SERIES
Print date 16.07.2020
Version 8.8 Revision date 23.05.2020

EN
Page 4 / 10

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

ethylbenzene

INDEX No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

TWA: 441 mg/m³; 100 ppm

STEL: 552 mg/m³; 125 ppm

Trichloromethane

INDEX No. 602-006-00-4 / EC No. 200-663-8 / CAS No. 67-66-3

TWA: 9,9 mg/m³; 2 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 180 mg/kg

DNEL acute inhalative (local), Workers: 289 mg/m³

DNEL acute inhalative (systemic), Workers: 442 mg/m³

DNEL long-term inhalative (local), Workers: 221 mg/m³

DNEL long-term inhalative (systemic), Workers: 211 mg/m³

2-ethoxy-1-methylethyl acetate

INDEX No. 603-177-00-8 / EC No. 259-370-9 / CAS No. 54839-24-6

DNEL long-term dermal (systemic), Workers: 103 mg/kg

DNEL acute inhalative (systemic), Workers: 608 mg/m³

DNEL long-term inhalative (systemic), Workers: 302 mg/m³

hydrocarbons, C9, aromatics

EC No. 918-668-5 / CAS No. 64742-95-6

DNEL long-term dermal (systemic), Workers: 25 mg/kg

DNEL long-term inhalative (systemic), Workers: 150 mg/m³

PNEC:

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

PNEC aquatic, freshwater: 0,327 mg/L

PNEC aquatic, marine water: 0,327 mg/L

PNEC sediment, freshwater: 12,64 mg/kg

PNEC sediment, marine water: 12,64 mg/kg

PNEC, soil: 2,31 mg/kg

PNEC sewage treatment plant (STP): 6,58 mg/L

2-ethoxy-1-methylethyl acetate

INDEX No. 603-177-00-8 / EC No. 259-370-9 / CAS No. 54839-24-6

PNEC aquatic, freshwater: 1,3 mg/L

PNEC aquatic, marine water: 0,13 mg/L

PNEC sediment, freshwater: 6,4 mg/kg

PNEC sediment, marine water: 0,64 mg/kg

PNEC, soil: 1,34 mg/kg

PNEC sewage treatment plant (STP): 62,5 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Article No.: T25
Print date 16.07.2020
Version 8.8

SERIE/SERIES
Revision date 23.05.2020

EN
Page 5 / 10

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Colour: refer to label

Odour: characteristic

Odour threshold: not determined

pH at 20 °C: not applicable

Melting point/freezing point: not determined

Initial boiling point and boiling range: 138 °C

Flash point: 25 °C
Method: DIN 53213-1 (08/2002: replaced by EN ISO 1523)

Evaporation rate: not determined

flammability

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 0,8 Vol-%

Upper explosion limit: 9,8 Vol-%

Vapour pressure at 20 °C: 30 mbar

Vapour density: not determined

Relative density:

Density at 20 °C: 1,07 g/cm³

Solubility(ies):

Water solubility (g/L) at 20 °C: insoluble

Partition coefficient: n-octanol/water: see section 12

Ignition temperature in °C 200 °C

Decomposition temperature: not applicable

Viscosity at 20 °C: > 90 s 4 mm
Method: DIN 53211

Explosive properties: not applicable

Oxidising properties: not applicable

9.2. Other information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: T25
Print date 16.07.2020
Version 8.8

SERIE/SERIES
Revision date 23.05.2020

EN
Page 6 / 10

Solid content (%): 61 weight-%
solvent content:
Organic solvents: 38 weight-%
Water: 1 weight-%
Solvent separation test (%): < 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

Xylene

oral, LD50, Rat 3523 - 4000 mg/kg
dermal, LD50, Rabbit: 12126 mg/kg
inhalative (vapours), LC50, Rat 6350 - 6700 mg/L (4 h)

ethylbenzene

oral, LD50, Rat: 3500 mg/kg
dermal, LD50, Rabbit: 15400 mg/kg

2-ethoxy-1-methylethyl acetate

oral, LD50, Rat: 5000 mg/kg
dermal, LD50, Rabbit: 13,42 mg/kg
inhalative (vapours), LC50, Rat: 6,99 mg/L (4 h)

hydrocarbons, C9, aromatics

oral, LD50, Rat: 3592 mg/kg
dermal, LD50, Rabbit: 3160 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: T25 SERIE/SERIES
Print date 16.07.2020
Version 8.8 Revision date 23.05.2020 EN
Page 7 / 10

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
Do not allow to enter into surface water or drains.

12.1. Toxicity

Xylene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2,6 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna: 1 mg/L (48 h)
Algae toxicity, ErC50, Selenastrum capricornutum: 2,2 mg/L (73 h)
Bacterial toxicity: NOEC, Activated sludge: 16 mg/L (28 d)
Method: OECD 301 F

ethylbenzene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 4,2 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna 1,8 - 2,4 mg/L (48 h)
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 5,4 mg/L (72 h)

2-ethoxy-1-methylethyl acetate

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 140 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna: 110 mg/L (48 h)
Algae toxicity, ErC50, green alga: > 100 mg/L (72 h)
Bacterial toxicity: EC10, Pseudomonas putida: 560 mg/L (16 h)

hydrocarbons, C9, aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 9,2 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna: 3,2 mg/L (48 h)

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Xylene

aerobic, OECD 301 F: 90 % (28 d)

2-ethoxy-1-methylethyl acetate

, OECD 301D: 100 % (28 d)

12.3. Bioaccumulative potential

Xylene

Partition coefficient: n-octanol/water: 3,12 - 3,2

Bioconcentration factor (BCF)

Xylene

Bioconcentration factor (BCF): 25,9

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: T25
Print date 16.07.2020
Version 8.8

SERIE/SERIES
Revision date 23.05.2020

EN
Page 8 / 10

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080312* waste ink containing dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1210

14.2. UN proper shipping name

Land transport (ADR/RID): Printing ink
Sea transport (IMDG): PRINTING INK
Air transport (ICAO-TI / IATA-DGR): Printing ink

14.3. Transport hazard class(es)

Land transport (ADR/RID): KEINE GÜTER DER KLASSE 3
in containers > 450 l: class 3, item 31c
Sea transport (IMDG): 3
for packages < 30 litres: Transport in accordance with the provisions of paragraph 2.3.2.5 of the
IMDG Cod e.
Air transport (ICAO-TI / IATA-DGR): 3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-D

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 405,609

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: T25
 Print date 16.07.2020
 Version 8.8

SERIE/SERIES
 Revision date 23.05.2020

EN
 Page 9 / 10

SECTION 16: Other information

Full text of classification in section 3:

| | | |
|---|--|---|
| Flam. Liq. 3 / H226 STOT SE 3 / H335 | Flammable liquids Specific target organ toxicity (single exposure) | Flammable liquid and vapour. May cause respiratory irritation. |
| Aquatic Chronic 2 / H411 Asp. Tox. 1 / H304 STOT SE 3 / H336 | Hazardous to the aquatic environment Aspiration hazard Specific target organ toxicity (single exposure) | Toxic to aquatic life with long lasting effects. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. |
| Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT RE 2 / H373 | Acute toxicity (dermal) Acute toxicity (inhalative) skin corrosion/irritation Serious eye damage/eye irritation Specific target organ toxicity (repeated exposure) | Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| Flam. Liq. 2 / H225 Carc. 2 / H351 | Flammable liquids Carcinogenicity | Highly flammable liquid and vapour. Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| Repr. 2 / H361 Acute Tox. 3 / H331 Acute Tox. 4 / H302 STOT RE 1 / H372 | Reproductive toxicity Acute toxicity (inhalative) Acute toxicity (oral) Specific target organ toxicity (repeated exposure) | Suspected of damaging the unborn child. Toxic if inhaled. Harmful if swallowed. Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

| | | |
|---------------------------|---|---|
| Flam. Liq. 3 STOT SE 3 | Flammable liquids Specific target organ toxicity (single exposure) | On basis of test data. Calculation method. |
| STOT SE 3 | Specific target organ toxicity (single exposure) | Calculation method. |
| Aquatic Chronic 3 | Hazardous to the aquatic environment | Calculation method. |

Abbreviations and acronyms

| | |
|-----------|---|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| OEL | Occupational Exposure Limit Value |
| BLV | Biological Limit Value |
| CAS | Chemical Abstracts Service |
| CLP | Classification, Labelling and Packaging |
| CMR | Carcinogenic, Mutagenic and Reprotoxic |
| DIN | German Institute for Standardization / German industrial standard |
| DNEL | Derived No-Effect Level |
| EAKV | European Waste Catalogue Directive |
| EC | Effective Concentration |
| EC | European Community |
| EN | European Standard |
| IATA-DGR | International Air Transport Association – Dangerous Goods Regulations |
| IBC Code | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk |
| ICAO-TI | International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air |
| IMDG Code | International Maritime Code for Dangerous Goods |
| ISO | International Organization for Standardization |
| LC | Lethal Concentration |
| LD | Lethal Dose |
| MARPOL | Maritime Pollution: The International Convention for the Prevention of Pollution from Ships |

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: T25 SERIE/SERIES
Print date 16.07.2020 EN
Version 8.8 Revision date 23.05.2020 Page 10 / 10

| | |
|-------|--|
| OECD | Organisation for Economic Cooperation and Development |
| PBT | persistent, bioaccumulative, toxic |
| PNEC | Predicted No Effect Concentration |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| UN | United Nations |
| VOC | Volatile Organic Compounds |
| vPvB | very persistent and very bioaccumulative |

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version